



FF15WAC

## FULLFLOW

FULLFLOW radiator valves are designed and manufactured to meet the requirements of commercial installations. They feature a non-rising spindle, double EPDM 'O' ring gland seals with an additional 'O' ring back seating arrangement, this enables the FULLFLOW valve to be serviced without the requirement for draining the system, perfect for commercial applications. The range includes compression and screwed iron connections, as well as drain off options. Straight and angle versions are also available.



FF15LACD

**DIMENSIONS**

**Wheel Head**

15mm & 1/2"/22mm & 3/4"  
Angle

15mm & 1/2"/22mm & 3/4" Straight  
(for horizontal mounting)

| Model                | A    | B    | C    | D    |
|----------------------|------|------|------|------|
|                      | (mm) | (mm) | (mm) | (mm) |
| 15mm & 1/2" Angle    | 55.5 | 39.0 | 54.8 | 40.0 |
| 22mm & 3/4" Angle    | 56.0 | 45.2 | 61.1 | 40.0 |
| 15mm & 1/2" Straight | 69.0 | 47.0 | 47.8 | 40.0 |
| 22mm & 3/4" Straight | 72.1 | 54.5 | 54.1 | 40.0 |

**Lockshield**

15mm & 1/2"/22mm & 3/4" Straight  
(for horizontal mounting)

15mm & 1/2" Angle  
with Drain Off

| Model                   | A    | B    | C    | D    | E    |
|-------------------------|------|------|------|------|------|
|                         | (mm) | (mm) | (mm) | (mm) | (mm) |
| 15mm & 1/2" Straight    | 62.0 | 47.0 | 47.8 | 34.0 | -    |
| 22mm & 3/4" Straight    | 65.1 | 54.5 | 54.1 | 34.0 | -    |
| 15mm & 1/2" Angle/Drain | 52.5 | 39.0 | 54.8 | 34.0 | 30.0 |

NB: All measurements are nominal.

**GENERAL SPECIFICATION**

- 1**

**CERTIFICATION**  
Produced under a quality management system - ISO 9001:2008. Conforms to BS 2767-10.
- 2**

**OPERATING PRESSURES**  
Tested to a maximum pressure of 10 bar.
- 3**

**OPERATING TEMPERATURE**  
Maximum 120°C.
- 4**

**DELIVERY**  
2 - 5 working days.
- 5**

**COLOUR**  
Finished in polished chrome or brass.
- 6**

**CONNECTIONS**  
Compression or screwed iron.



FF15WSC

For more general information, please see page 250.

| Description                      | Metal Finish    | Wheel Head Order Code | Lockshield Order Code | Minimum Order Qty |
|----------------------------------|-----------------|-----------------------|-----------------------|-------------------|
| 15mm & 1/2" Angle                | Brass           | FF15WAB               | FF15LAB               | 10                |
| 15mm & 1/2" Angle                | Polished Chrome | FF15WAC               | FF15LAC               | 10                |
| 15mm & 1/2" Angle with Drain Off | Polished Chrome | -                     | FF15LACD              | 10                |
| 15mm & 1/2" Straight             | Brass           | FF15WSB               | FF15LSB               | 10                |
| 15mm & 1/2" Straight             | Polished Chrome | FF15WSC               | FF15LSC               | 10                |
| 22mm & 3/4" Angle                | Brass           | FF22WAB               | FF22LAB               | 5                 |
| 22mm & 3/4" Angle                | Polished Chrome | FF22WAC               | FF22LAC               | 5                 |
| 22mm & 3/4" Straight             | Polished Chrome | FF22WSC               | FF22LSC               | 5                 |