



FULLFLOW

FULLFLOW radiator valves are designed and manufactured to meet the requirements of commercial installations.

They feature a non-rising spindle, double EPDM 'O' ring gland seals with an additional 'O' ring back seating arrangement, this enables the FULLFLOW valve to be serviced without the requirement for draining the system, perfect for commercial applications. The range includes compression and screwed iron connections, as well as drain off options. Straight and angle versions are also available.



FF15WAC




FF15LACD


Dimensions

Wheel Head

15mm or 1/2"/22mm or 3/4" BSP Angle




15mm or 1/2"/22mm or 3/4" BSP Straight (for horizontal mounting)




Model	A	B	C	D
	(mm)	(mm)	(mm)	(mm)
15mm or 1/2" BSP Angle	55.5	39.0	54.8	40.0
22mm or 3/4" BSP Angle	56.0	45.2	61.1	40.0
15mm or 1/2" BSP Straight	69.0	47.0	47.8	40.0
22mm or 3/4" BSP Straight	72.1	54.5	54.1	40.0

Lockshield

15mm or 1/2"/22mm or 3/4" BSP Straight (for horizontal mounting)



15mm or 1/2" BSP Angle with Drain Off



Model	A	B	C	D	E
	(mm)	(mm)	(mm)	(mm)	(mm)
15mm or 1/2" BSP Straight	62.0	47.0	47.8	34.0	-
22mm or 3/4" BSP Straight	65.1	54.5	54.1	34.0	-
15mm or 1/2" BSP Angle/Drain	52.5	39.0	54.8	34.0	30.0

NB: All measurements are nominal.

General specification

CERTIFICATION
Produced under a quality management system - ISO 9001:2008. Conforms to BS 2767-10.

GUARANTEE
2 year guarantee from date of purchase against manufacturing defects.

COLOUR
Finished in polished chrome or brass.

CONNECTIONS
Compression or screwed iron.

OPERATING PRESSURES
Tested to a maximum pressure of 10 bar.

OPERATING TEMPERATURE
Maximum 120°C.

DELIVERY
2 - 5 working days.



For more general information, please see page 260.

FULLFLOW

Description	Metal Finish	Wheel Head Order Code	Lockshield Order Code	Minimum Order Qty
15mm or 1/2" BSP Angle	Brass	FF15WAB	FF15LAB	10
15mm or 1/2" BSP Angle	Polished Chrome	FF15WAC	FF15LAC	10
15mm or 1/2" BSP Angle with Drain Off	Polished Chrome	-	FF15LACD	10
15mm or 1/2" BSP Angle with Drain Off	Brass	-	FF15LABD	10
15mm or 1/2" BSP Straight	Brass	FF15WSB	FF15LSB	10
15mm or 1/2" BSP Straight	Polished Chrome	FF15WSC	FF15LSC	10
22mm or 3/4" BSP Angle	Brass	FF22WAB	FF22LAB	5
22mm or 3/4" BSP Angle	Polished Chrome	FF22WAC	FF22LAC	5
22mm or 3/4" BSP Straight	Polished Chrome	FF22WSC	FF22LSC	5
22mm or 3/4" BSP Straight	Brass	-	FF22LSB	5
Wheelhead Valve Top Only	White Plastic	FFTOPWH	-	20
Lockshield Valve Top Only	White Plastic	-	FFTOPLS	20